



**STANDARD DETAIL NOTES:**

THIS IS A DIAGRAMMATIC REPRESENTATION AND CERTAIN DETAILS REMOVED FOR CLARITY.

**IMPORTANT:** ALL DIMENSIONS INDICATED ARE NOMINAL.

ESTIMATED O/A ASSEMBLY DRY WEIGHT: 0.55kW 4P - 104.00kg's, 0.75kW 4P - 105.00kg's

**IMPORTANT:**  
THIS DATA IS RELEASED FOR  
REFERENCE ONLY.

REVISION		THIS DATA REMAINS THE PROPERTY OF STALKER ENGINEERING. NO DATA MAY BE REPRODUCED WITHOUT PRIOR CONSENT OF COMPANY. DATA MAY BE ALTERED WITHOUT NOTIFICATION.	<b>GENERAL TOLERANCES</b> METRIC +/-0.400mm IMPERIAL +/-0.015"	DRWN: AR	 <b>STALKER PUMPS</b> <a href="http://www.stalkerpumps.com.au">www.stalkerpumps.com.au</a>
		AS1100 3rd ANGLE PROJECTION	REFERENCE:	DATE: 19/07/2007	
		<b>DO NOT SCALE</b>	APPRVD:	CHECKED:	
				FILE REF: REFER DWG NUMBER	DIMENSION OUTLINE DIAGRAMMATIC ISO 50/32-160 DC JAW SPACER COUPLING 0.55 & 0.75kW 4P 80 BASE FRAME MOUNTED DRAWING No: <b>1900ISODCJAWSPCLEM030031BFDIMA3</b>
					<b>A3</b>